SPARTAN CHEMICALS

11 Spring Gardens Silsden, Keighley West Yorkshire BD20 0DJ Landline 01535657621 **MOBILE 07 774 480335** E.Mail <u>billeagleson76@gmail.com</u>

E-MAIL sales@spartanchemicals.co.uk

Web Site www.spartanchemicals.co.uk

RUST GUARD MT RP 805

Rust Guard MT is a solvent blend designed to effectively de-water, and provide a soft rust protective film. It is a high solids product containing a blend of lanolin grease and surface active de-watering and corrosion inhibiting agents dispersed in white spirit, and meets the composition and performance requirements of BS 1133 Section 6, and in reasonable conditions for indoor storage will give indefinite protection.

Rust Guard MT has a pleasant characteristic smell and is suitable for use on all metals. Care should be taken with some plastic and rubber materials.

DIRECTIONS FOR USE.

Use as supplied by, brush, non misting spray, or immersion

CHARACTERISTICS

Appearance Solubility Specific Gravity Flash point Film thickness Coverage Rate Corrosive action Clear brown liquid Insoluble in water 0.79 39c Abel Closed Cup. 0.0091mm 225 sq. meters per 5 ltrs None on metals but may effect some plastics or rubbers

HEALTH AND SAFETY INFORMATION

Safety Advice

Flammable Substance identification No 1993 do not breath spray. Avoid unnecessary or prolonged personal contact, Keep out of reach of children.Do not mix with other chemical products unless specifically directed. **First Aid**

Wash splashes from the skin immediately with soap and water. If swallowed, **DO NOT INDUCE VOMITING.** give water to drink. Medical attention is recommended following eye contact, excessive levels of vapour, or if the product is swallowed.

Spillage's Spillage's should be contained and absorbed with an inert mineral product.

Additional information Do not spray onto hot surfaces, live electrical equipment, or naked flame