

SPARTAN CHEMICALS

11 Spring Gardens
Silsden, Keighley
West Yorkshire
BD20 0DJ
Landline 01535657621
MOBILE 07 774 480335

E.Mail billeagleson76@gmail.com

E-MAIL sales@spartanchemicals.co.uk

Web Site www.spartanchemicals.co.uk

RUST GUARD LT RP 810

Rust Guard LT is a solvent deposited water displacing wax film rust preventative. It is a very high solids product giving extended protection in difficult conditions.

Rust Guard LT is suitable for use on all metals, and is particularly effective for medium to long term protection of components during storage or transit. It is also suitable for application to painted surfaces, although it is advisable to check compatibility with the paint prior to use

DIRECTIONS FOR USE.

Use as supplied by, brush, non misting spray, or immersion. Care should be taken in spray applications, as the heavy duty nature of the product may block spray jets. Drying time is approximately 40-50 minutes.

CHARACTERISTICS

Appearance	Brown liquid
Solubility	Insoluble in water
Specific Gravity	0.850
Flash point	35c Abel Closed Cup.
Film thickness	2 microns
Coverage Rate	Dependant on method of application

HEALTH AND SAFETY INFORMATION

Safety Advice

Flammable Substance identification No 1993 do not breath spray. Avoid unnecessary or prolonged personal contact, Keep out of reach of children. Do not mix with other chemical products unless specifically directed.

First Aid

Wash splashes from the skin immediately with soap and water. If swallowed, **DO NOT INDUCE VOMITING.** give water to drink. Medical attention is recommended following eye contact, excessive levels of vapour, or if the product is swallowed.

Spillage's Spillage's should be contained and absorbed with an inert mineral product.

Additional information Do not spray onto hot surfaces, live electrical equipment, or naked flame